



ABRASION RUBBER

Quality	Features	Dimensions Thickness/width/length	Abrasion mm ³	SPECIFICATIONS						RESISTANCE				
				Colour	Density g/cm ³	Shore A	Tensile strength (MPa)	Elongation %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
ABRASION RUBBER - QUALITIES														
SSG40	High grade soft abrasion rubber with excellent mechanical properties, abrasion resistance and tensile strength.	1-10 mm = 1,4 x10 mtr 12-20 mm = 1,4 x 5 mtr	118	Black	1,0	40	19	600	-20/+70	-	-	0	0	0
RSG45	High grade soft abrasion rubber with excellent mechanical properties, abrasion resistance and tensile strength.	4-10 mm = 1,4 x10 mtr 12-30 mm = 1,4 x 5 mtr 40-50 mm = 1,4 x2,5 mtr or 40-50 mm = 1,4 x 5 mtr (available with bonding layer)	110	Red	1,1	45	16	600	-20/+90	-	-	0	0	0
SSG60	High grade abrasion rubber with excellent mechanical properties, abrasion resistance and tensile strength.	2 mm = 1,4 x 20 mtr 4-10 mm = 1,4 x 10 mtr 12-30 mm = 1,4 x 5 mtr 40-50 mm = 1,4 x 2,5 mtr or 40-50 mm = 1,4x5 mtr (Available with bonding layer. Available in 2000 mm without bonding layer)	120	Black	1,2	60	15	400	-30/-70	-	-	0	0	0

RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations