



RUBBER SHEETING EPDM/SBR

				SPECIFICATIONS						RESISTANCE				
Quality	Features	Dimensions Thickness/width/length	Inserts (no.)	Colour	Density g/cm ³	Shore A	Tensile strength (MPA)	Elongation %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
EPDM/SBR QUALITIES														
EPDM/SBR 40	Very soft EPDM quality with good resistance to ageing, ozone, acid and lye	1-10 mm = 1,4x10 mtr 12-25 mm = 1,4x5 mtr 30-50 mm = 1,4x2,5 mtr	None	Black	1,35	42	7	550	-25/+100	-	-	+	+	+
EPDM/SBR 50	Soft EPDM quality with good resistance to ageing, ozone, acid and lye	1-2 mm = 1,4x20 mtr 3-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,2/1,4x2,5 mtr or 40-50 mm = 1,4x5 mtr	None	Black	1,35	50	5	300	-30/+90	-	-	+	+	+
EPDM/SBR 65	Medium hard EPDM quality with good resistance to ageing, ozone, acid and lye	1-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,4x2,5 mtr or 40-50 mm = 1,4x5 mtr	None 1 insert 2 inserts	Black	1,4	65	3,5	250	-20/-90	-	-	+	+	+
EPDM/SBR 80	Hard EPDM quality with good resistance to ageing, ozone, acid and lye	1-2 mm = 1,4 x 20 mtr 3-10 mm = 1,4 x 10 mtr	None	Black	1,3	80	5	200	-20/+90	-	-	+	+	+
EPDM Super 70 E9614	Medium hard EPDM quality with excellent resistance to ageing, ozone, acid and lye	1-2 mm = 1,4x 20 mtr 3-6 mm = 1,4x10 mtr 8 mm = 1,4x 5 mtr	None	Black	1,22	70	9	200	-40/+120	-	-	++	++	++
EPDM Varme KTW70 E628	Medium hard EPDM quality with excellent resistance to ageing, ozone, acid and lye. Drinking water gaskets KTW 1.3.13 D1 u. D2 cold and warm water	1-2 mm = 1,4x 20 mtr 3-6 mm = 1,4x10 mtr 8-10 mm = 1,4x 5 mtr	None	Black	1,12	70	11	250	-40/+120	-	-	++	++	++
EPDM 60 FDA	FDA approved EPDM quality with good resistance to ageing, ozone, acid and lye	1-2 mm = 1,4x 20 mtr 3-10 mm = 1,4x10 mtr 12-50 mm = 1,4x 5 mtr	None	White	1,45	60	5	300	-30/+100	-	-	+	+	+
RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT														

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations