



## RUBBER SHEETING NBR/SBR

Quality	Features	Dimensions Thickness/width/length	Inserts (no.)	SPECIFICATIONS						RESISTANCE				
				Colour	Density g/cm <sup>3</sup>	Shore A	Tensile strength (MPA)	Elongation %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
<b>NBR/SBR QUALITIES</b>														
NBR/SBR50	Soft perbunan quality with good oil & fat resistant properties.	1-2 mm = 1,4x20 mtr 3-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,4x2,5 mtr or 40-50 mm = 1,4x5 mtr	None	Black	1,35	50	4	250	-20/+70	+	-	0	0	-
NBR/SBR65	Medium hard. perbunan quality with good oil & fat resistant properties.	1-2 mm = 1,2/1,4x20 mtr 3-10 mm = 1,2/1,4x10 mtr 12-30 mm = 1,2/1,4x5 mtr 40-50 mm = 1,2/1,4x2,5 mtr or 40-50 mm = 1,4x5 mtr	None 1 insert 2 inserts	Black	1,5	65	4	250	-20/+70	+	-	0	0	-
NBR/SBR80	Hard perbunan quality with good oil & fat resistant properties.	1-2 mm = 1,4x20 mtr 3-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,4x2,5 mtr	None	Black	1,5	80	4	250	-20/+70	+	-	0	0	-
<b>RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT</b>														

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations