

# SBK



## SKANKOP PP 800/4 HOT OIL 2+2



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 180 mm<sup>3</sup>



Material temperature  
-20°/+100° C (short peaks -25°/+120° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



Max oil resistant for materials with animal,  
vegetable & mineral oils



Flame resistant acc. to ISO340 "K"



SPECS	FACTS
Tensile strength N/mm	<b>800</b>
Recommended max. working load N/mm	<b>50 (due to fabric type)</b>
Covers mm	2+2
Quality designation	HOT-OIL
Rubber quality covers	NBR
Rubber quality core	NBR
Colour	Black
No. of fabrics	4
Fabric type	EP200
Warp	Polyester
Weft	Polyester
Elongation max. %	2,5
Total thickness app. mm	9,3
Weight kg/m <sup>2</sup> app.	12,3
Min. pulley Ø 60-100% utilization of working load	500
Min. pulley Ø 30-60% utilization of working load	400
Smaller pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*