


# SBK



## SKANKOP EP 630/3 1+3 OIL-GS-K



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 200 mm<sup>3</sup>



Material temperature  
-20°/+80° C (short peaks -30°/+90° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



Excellent oil resistance to materials containing  
animal, vegetable & mineral oils and fats.



Flame resistant acc. to ISO340 "K"

SPECS	FACTS
Tensile strength N/mm	630
Recommended max. working load N/mm	57
Covers mm	1+3
Quality designation	OIL-GS-K
Rubber quality covers	NBR
Rubber quality core	NBR
Colour	Black
No. of fabrics	3
Fabric type	EP200
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	8,0
Weight kg/m <sup>2</sup> app.	9,2
Min. pulley Ø 60-100% utilization of working load	500
Min. pulley Ø 30-60% utilization of working load	400
Smaller pulleys	Please contact us
REMARKS:	Available in 150,200,250,300,315 mm <b>MOLDED EDGES!</b>
IMPORTANT !	At the assembly, the thick side of the belt (3 mm) must face the pulley

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*