

# SBK



## SKANKOP EP 630/3 1+3 OIL-GS-K-ME



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 200 mm<sup>3</sup>



Material temperature  
-20°/+80° C (short peaks -30°/+90° C)



Ambient temperature  
In principle as for material but with limitations [See more](#)



Excellent oil resistance to materials containing  
animal, vegetable & mineral oils and fats



Flame resistant acc. to ISO340 "K"



### SPECIFICATIONS

Tensile strength N/mm	630
Recommended max. working load N/mm	57
Covers mm	1+3
Quality designation	OIL-GS-K-ME
Rubber quality covers	NBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	3
Fabric type	EP125
Warp	Polyester
Weft	Polyamid
Elongation max. %	2.5
Total thickness app. mm	7.5
Weight kg/m <sup>2</sup> app.	8.6
Min. pulley Ø 60-100% utilization of working load	500
Min. pulley Ø 30-60% utilization of working load	400
Smaller pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations*