


SBK



SKANKOP EP 1250/5 2+2 OIL-GS



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 150 mm³



Material temperature
-20°/+100° C (short peaks -30°/+120° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Excellent oil resistance to materials containing
animal, vegetable & mineral oils and fats.

SPECS	FACTS
Tensile strength N/mm	1250
Recommended max. working load N/mm	114
Covers mm	2+2
Quality designation	OIL-GS
Rubber quality covers	NBR
Rubber quality core	NBR
Colour	Black
No. of fabrics	5
Fabric type	EP250
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	12,5
Weight kg/m ² app.	14,4
Min. pulley Ø 60-100% utilization of working load	1000
Min. pulley Ø 30-60% utilization of working load	800
Smaller pulleys	Please contact us

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.