

# SBK



## SKANKOP EP 1000/4 1+3 Y



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 150 mm<sup>3</sup>



Material temperature  
-30°/+70° C (short peaks -40°/+80° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)

| SPECS   | FACTS   |
|---|---|
| Tensile strength N/mm                             | <b>1000</b>   |
| Recommended max. working load N/mm                | <b>91</b>   |
| Covers mm   | 1+3   |
| Quality designation                               | Y   |
| Rubber quality covers                             | SBR   |
| Rubber quality core                               | SBR   |
| Colour  | Black   |
| No. of fabrics                                    | 4   |
| Fabric type                                       | EP250   |
| Warp  | Polyester   |
| Weft  | Polyamid  |
| Elongation max. %                                 | 2,5   |
| Total thickness app. mm                           | 10,5  |
| Weight kg/m <sup>2</sup> app.                     | 12,1  |
| Min. pulley Ø 60-100% utilization of working load | 800   |
| Min. pulley Ø 30-60% utilization of working load  | 630   |
| Smaller pulleys                                   | Please contact us   |
| <b>IMPORTANT !</b>                                | At the assembly, the thick side of the belt (3 mm) must face the pulley |

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*