

# SBK



## SKANPLY EP 200/2 3+0 Supergrip Beige



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Material temperature  
-15°/+70° C (short peaks -20°/+80° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)

SPECS	FACTS
Tensile strength N/mm	<b>200</b>
Recommended max. working load N/mm	<b>20</b>
Covers mm	3+0
Quality designation	Y
Rubber quality covers	NR/SBR – supergrip profile
Rubber quality core	SBR
Colour	Beige
No. of fabrics	2
Fabric type	EP100
Warp	Polyester
Weft	Polyamid
Elongation max. %	1,5
Total thickness app. mm	6,7
Weight kg/m <sup>2</sup> app.	5,0
Min. pulley Ø 60-100% utilization of working load	250
Min. pulley Ø 30-60% utilization of working load	200
Min. pulley Ø < 30% utilization of working load	160
Smaller pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*