



## RUBBER SHEETING NR/SBR

				SPECIFICATIONS						RESISTANCE				
Quality	Features	Dimensions Thickness/width/length	Inserts (no.)	Colour	Density g/cm <sup>3</sup>	Shore A	Tensile strength (MPa)	Elonga- tion %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
<b>NR/SBR QUALITIES</b>														
NR/SBR 50	Soft standard quality with good mechanical properties	1-2 mm = 1,4x20 mtr 3-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,4x2,5 mtr or 40-50 mm = 1,4x5 mtr	None	Black	1,5	50	3	300	-20/+70	-	-	-	0	-
NR/SBR 65	Medium hard standard quality with good mechanical properties	1-10 mm = 1,2/1,4x10 mtr 12-30 mm = 1,2/1,4x5 mtr 40-50 mm = 1,2/1,4x2,5 mtr or 40-50 mm = 1,2/1,4x5 mtr	None 1 insert 2 inserts	Black	1,5	65	3	200	-20/+90	-	-	-	0	-
NR/SBR 80	Hard standard quality with good mechanical properties	1-2 mm = 1,4x20 mtr 3-10 mm = 1,4x10 mtr 12-30 mm = 1,4x5 mtr 40-50 mm = 1,4x2,5 mtr	None	Black	1,5	80	3	200	-30/-70	-	-	-	0	-
NR/SBR45 FDA-CFR 177.2600	Soft food quality. Meets positive list FDA CFR 177.2600 Suitable for long-lasting contact with food	1-2 mm = 1,4x20 mtr 3-6 mm = 1,4x10 mtr	None	White	1,28	45	12	550	-30/-70	-	-	-	0	-
NR/SBR60 BGA Cat. 4	Medium hard food quality acc. to BgVV XXI(BGA), category 4	1-2 mm = 1,4x20 mtr 3-6 mm = 1,4x10 mtr	None	White	1,43	65	8	550	-30/-70	-	-	-	0	-
<b>RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT</b>														

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations