



SIDE SKIRT RUBBER

Quality	Features	Dimensions Thickness/width/length	Abrasion mm ³	SPECIFICATIONS						RESISTANCE				
				Colour	Density g/cm ³	Shore A	Tensile strength (MPA)	Elongation %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
SIDE SKIRT RUBBER QUALITIES														
RKG45	High grade soft rubber with good mechanical properties, abrasion resistance and tensile strength.	Thickness: 6/8/10/12/15/20 mm x 20 mtr Width: 60,80,100,120,150,200 mm (different width and thickness upon request)	175	Red	1,25	45	6	550	-25/+80	-	-	-	0	0
SKG65	High grade rubber with excellent mechanical properties, abrasion resistance and tensile strength.	Thickness: 6/8/10/12/15/20 mm x 20 mtr Width: 60,80,100,120,150,200 mm (different width and thickness upon request)	120	Black	1,2	65	15	350	-20/+70	-	-	-	0	0
SKG60	Side skirt rubber with good mechanical properties and fair abrasion resistance. Gentle towards the belt cover	Thickness: 6/8/10/12/15/20 mm x 20 mtr Width: 60,80,100,120,150,200 mm (different width and thickness upon request)	300	Black	1,27	60	6	300	-30/+80	-	-	-	0	0
RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT														

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations