



SILICONE

				SPECIFICATIONS						RESISTANCE				
Quality	Features	Dimensions Thickness/width/length	Inserts (no.)	Colour	Density g/cm ³	Shore A	Tensile strength (MPa)	Elongation %	Temp. range C°	Oil	Benzine	Acid	Lye	Ageing (weather, ozone etc.)
SILICONE QUALITIES														
Silicone R40 Red	Soft standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Red	1,15	40	6	350	-60/+220	0	0	++	++	++
Silicone R60 Red	Standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Red	1,15	60	6	350	-60/+220	0	0	++	++	++
Silicone T40 Transparent	Soft standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Black	1,15	40	5	350	-60/+220	0	0	++	++	++
Silicone T50 Transparent	Soft standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Transparent	1,15	50	5	350	-60/+220	0	0	++	++	++
Silicone T60 Transparent	Standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Transparent	1,15	60	5	350	-60/+220	0	0	++	++	++
Silicone S60 Black	Standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Black	1,15	40	5	350	-60/+220	0	0	++	++	++
Silicone B60 Blue	Standard quality with excellent heat and cold resistance as well as good resistance to ageing, ozone, acid and lye	1-6 mm = 1,2 x 10 mtr 8-10 mm = 1,2 x 5 mtr	None	Blue	1,15	40	5	350	-60/+220	0	0	++	++	++
RESISTANCE: ++ = EXCELLENT RESISTANCE / + = GOOD RESISTANCE / 0 = LIMITED RESISTANCE / - = NOT RESISTANT														

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk • www.sbk-belt.dk

Subject to alterations