


SBK



SKANKOP EP 630/3 1+3 ATEX-OIL-GM



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 170 mm³



Material temperature
-20°/+70° C (short peaks -25°/+80° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Good oil resistance to materials containing
animal & vegetable oils and fats.



Flame resistant acc. to ISO340 "K"



SPECS	FACTS
Tensile strength N/mm	630
Recommended max. working load N/mm	57
Covers mm	1+3
Quality designation	ATEX-OIL-GM
Rubber quality covers	NBR/SBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	3
Fabric type	EP200
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	8,4
Weight kg/m ² app.	9,0
Min. pulley Ø 60-100% utilization of working load	500
Min. pulley Ø 30-60% utilization of working load	400
Smaller pulleys	Please contact us
IMPORTANT !	At the assembly, the thick side of the belt (3 mm) must face the pulley



Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.