


SBK



SKANKOP EP 800/4 1+3 OIL-GM-K



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 200 mm³



Material temperature
-25°/+70° C (short peaks -30°/+80° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Good oil resistance to materials containing
animal & vegetable oils and fats.



Flame resistant acc. to ISO340 "K"

SPECS	FACTS
Tensile strength N/mm	800
Recommended max. working load N/mm	72
Covers mm	1+3
Quality designation	OIL-GM-K
Rubber quality covers	NBR/SBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	4
Fabric type	EP160
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	8,0
Weight kg/m ² app.	9,2
Min. pulley Ø 60-100% utilization of working load	630
Min. pulley Ø 30-60% utilization of working load	500
Smaller pulleys	Please contact us

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.