


# SBK



## SKANKOP EP 630/5 1+1 OIL-GM-S



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 200 mm<sup>3</sup>



Material temperature  
-25°/+70° C (short peaks -30°/+80° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



Good oil resistance to materials containing  
animal & vegetable oils and fats.



Flame resistant acc. to ISO340 "S"

| SPECS   | FACTS             |
|---|-------------------|
| Tensile strength N/mm                             | <b>630</b>        |
| Recommended max. working load N/mm                | <b>57</b>         |
| Covers mm   | 1+1               |
| Quality designation                               | OIL-GM-S          |
| Rubber quality covers                             | NBR/SBR           |
| Rubber quality core                               | SBR               |
| Colour  | Black             |
| No. of fabrics                                    | 5                 |
| Fabric type                                       | EP125             |
| Warp  | Polyester         |
| Weft  | Polyamid          |
| Elongation max. %                                 | 2,5               |
| Total thickness app. mm                           | 7,5               |
| Weight kg/m <sup>2</sup> app.                     | 8,6               |
| Min. pulley Ø 60-100% utilization of working load | 500               |
| Min. pulley Ø 30-60% utilization of working load  | 400               |
| Smaller pulleys                                   | Please contact us |

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*