


# SBK



## SKANKOP EP 500/3 1+1 OIL-GM



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 200 mm<sup>3</sup>



Material temperature  
-20°/+80° C (short peaks -25°/+90° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



Good oil resistance to materials containing  
animal & vegetable oils and fats.

SPECS	FACTS
Tensile strength N/mm	<b>500</b>
Recommended max. working load N/mm	<b>45</b>
Covers mm	1+1
Quality designation	OIL-GM
Rubber quality covers	NBR/SBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	3
Fabric type	EP160
Warp	Polyester
Weft	Polyamid
Elongation max. %	1,5
Total thickness app. mm	5,5
Weight kg/m <sup>2</sup> app.	6,3
Min. pulley Ø 60-100% utilization of working load	400
Min. pulley Ø 30-60% utilization of working load	315
Smaller pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*