


SBK



SKANKOP EP 630/5 1+1 OIL-GS-K



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 200 mm³



Material temperature
-20°/+80° C (short peaks -30°/+90° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Excellent oil resistance to materials containing
animal, vegetable & mineral oils and fats.



Flame resistant acc. to ISO340 "K"

SPECS	FACTS
Tensile strength N/mm	630
Recommended max. working load N/mm	57
Covers mm	1+1
Quality designation	OIL-GS-K
Rubber quality covers	NBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	5
Fabric type	EP125
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	7,5
Weight kg/m ² app.	8,6
Min. pulley Ø 60-100% utilization of working load	500
Min. pulley Ø 30-60% utilization of working load	400
Smaller pulleys	Please contact us

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.