

SBK



SKANKOP EP 800/3 1+3 OIL-GS-K-ME



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 200 mm³



Material temperature
-20°/+80° C (short peaks -30°/+90° C)



Ambient temperature
In principle as for material but with limitations [See more](#)



Excellent oil resistance to materials containing
animal, vegetable & mineral oils and fats



Flame resistant acc. to ISO340 "K"

SPECIFICATIONS

Tensile strength N/mm	800
Recommended max. working load N/mm	72
Covers mm	1+3
Quality designation	OIL-GS-K-ME
Rubber quality covers	NBR
Rubber quality core	SBR/NBR
Colour	Black
No. of fabrics	3
Fabric type	EP160
Warp	Polyester
Weft	Polyamid
Elongation max. %	2.5
Total thickness app. mm	8.0
Weight kg/m ² app.	9.2
Min. pulley Ø 60-100% utilization of working load	630
Min. pulley Ø 30-60% utilization of working load	500
Smaller pulleys	Please contact us

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations