

# SBK



## SKANKOP EP 1250/4 1+3 OIL-GS



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 150 mm<sup>3</sup>



Material temperature  
-20°/+100° C (short peaks -30°/+120° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



Excellent oil resistance to materials containing  
animal, vegetable & mineral oils and fats.

SPECS	FACTS
Tensile strength N/mm	<b>1250</b>
Recommended max. working load N/mm	<b>114</b>
Covers mm	1+3
Quality designation	OIL-GS
Rubber quality covers	NBR
Rubber quality core	NBR
Colour	Black
No. of fabrics	4
Fabric type	EP315
Warp	Polyester
Weft	Polyamid
Elongation max. %	2,5
Total thickness app. mm	11,5
Weight kg/m <sup>2</sup> app.	13,2
Min. pulley Ø 60-100% utilization of working load	800
Min. pulley Ø 30-60% utilization of working load	630
Smaller pulleys	Please contact us
<b>IMPORTANT !</b>	At the assembly, the thick side of the belt (3 mm) must face the pulley

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*