

SBK



SKANPLY EP 250/2 3+1 ATEX-FCM-OIL-GS



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 200 mm³



Material temperature
-20°/+80° C (short peaks -25°/+100° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Max oil resistant for materials with animal,
vegetable & mineral oils



In accordance with EC 1935-2004 (all food types)



Flame resistant acc. to ISO340 "K"

| SPECS | FACTS |
|---|-------------------|
| Tensile strength N/mm | 250 |
| Recommended max. working load N/mm | 25 |
| Covers mm | 3+1 |
| Quality designation | ATEX-FCM-OIL-GS |
| Rubber quality covers | NBR/PVC |
| Rubber quality core | NBR/PVC |
| Colour | White |
| No. of fabrics | 2 |
| Fabric type | EP125 |
| Warp | Polyester |
| Weft | Polyamid |
| Elongation max. % | 1,5 |
| Total thickness app. mm | 6,2 |
| Weight kg/m ² app. | 8,9 |
| Min. pulley Ø 60-100% utilization of working load | 250 |
| Min. pulley Ø 30-60% utilization of working load | 200 |
| Min. pulley Ø < 30% utilization of working load | 160 |
| Smaller pulleys | Please contact us |



Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.