

SBK



SKANPLY EP 630/4 6+2 OIL-GS



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 150 mm³



Material temperature
-20°/+100° C (short peaks -30°/+120° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Excellent oil resistance to materials containing
animal, vegetable & mineral oils and fats.

| SPECS | FACTS |
|--|-------------------|
| Tensile strength N/mm | 630 |
| Recommended max. working load N/mm | 63 |
| Covers mm | 6+2 |
| Quality designation | OIL-GS |
| Rubber quality covers | NBR |
| Rubber quality core | NBR |
| Colour | Black |
| No. of fabrics | 4 |
| Fabric type | EP160 |
| Warp | Polyester |
| Weft | Polyamid |
| Elongation max. % | 2,5 |
| Total thickness app. mm | 12,0 |
| Weight kg/m ² app. | 15,0 |
| Min. pulle Ø 60-100% utilization of working load | 500 |
| Min. pulley Ø 30-60% utilization of working load | 400 |
| Min. pulley Ø < 30% utilization of working load | 315 |
| Smaller pulleys | Please contact us |

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.