

SBK



SKANPLY EP 400/3 4+2 S



Antistatic acc. to EN ISO 284:2012
($\leq 3 \times 10^8$ Ohm)



Abrasion max. 150 mm³



Material temperature
-30°/+60° C (short peaks -35°/+70° C)



Ambient temperature
Min/max. -20°/+50° C / [See more](#)



Flame resistant acc. to ISO340 "S"

SPECS	FACTS
Tensile strength N/mm	400
Recommndd max. working load N/mm	40
Covers mm	4+2
Quality designation	S
Rubber quality covers	SBR
Rubber qualtiy core	SBR
Colour	Black
No. of fabrics	3
Fabric type	EP125
Warp	Polyester
Weft	Polyamid
Elongation max. %	1,5
Total thickness app. mm	9,0
Weight kg/m ² app.	10,4
Min. pulley Ø 60-100% utilization of working load	315
Min. pulley Ø 30-60% utilization of working load	250
Min. pulley Ø < 30% utilization of working load	200
Smaller pulleys	Please contact us

Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

Subject to alterations.