

# SBK



## SKANPLY EP 400/3 4+2 T150



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)




Abrasion max. 180 mm<sup>3</sup>



Material temperature  
-30°/+150° C (short peaks -35°/+170° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



SPECS	FACTS
Tensile strength N/mm	<b>400</b>
Recommended max. working load N/mm	<b>40</b>
Covers mm	4+2
Quality designation	T150
Rubber quality covers	SBR
Rubber quality cpre	SBR
Colour	Black
No. of fabrics	3
Fabric type	EP125
Warp	Polyester
Weft	Polyamid
Elongation max. %	1,5
Total thickness app. mm	9,0
Weight kg/m <sup>2</sup> app.	10,4
Min. pulley Ø 60-100% utilization of working load	315
Min. pulley Ø 30-60% utilization of working load	250
Min. pulley Ø < 30% utilization of working load	200
Smalle pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*