


# SBK



## SKANPLY EP 250/2 3+1,5 Y



Antistatic acc. to EN ISO 284:2012  
( $\leq 3 \times 10^8$  Ohm)



Abrasion max. 150 mm<sup>3</sup>



Material temperature  
-30°/+70° C (short peaks -40°/+80° C)



Ambient temperature  
Min/max. -20°/+50° C / [See more](#)



SPECS	FACTS
Tensile strength N/mm	<b>250</b>
Recommended max. Working load N/mm	<b>25</b>
Covers mm	3+1,5
Quality designation	Y
Rubber quality covers	SBR
Rubber quality core	SBR
Colour	Black
No. of fabrics	2
Fabric type	EP125
Warp	Polyester
Weft	Polyamid
Elongation max. %	1,5
Total thickness app. mm	6,5
Weight kg/m <sup>2</sup> app.	7,6
Min. pulley Ø 60-100% utilization of working load	250
Min. pulley Ø 30-60% utilization of working load	200
Min. pulley Ø < 30% utilization of working load	160
Smaller pulleys	Please contact us

### Skandinavisk Båndkompagni A/S

Birkegårdsvej 34A • DK 8361 Hasselager • Tel. +45 8734 7080 • info@sbk-belt.dk www.sbk-belt.dk

*Subject to alterations.*